




2' AND 4' DIMMABLE LED REPLACEMENT BULBS



The AccelTex Solutions EnergyLynk Replacement LED Bulbs are used to replace burnt out LED bulbs and are fully compatible for use with the AccelTex Solutions Dimmable Wireless Light/Load Controller and LED Dimmable Driver. These bulbs provide smooth dimming and no-flicker light operation.

| | ATS-LEDB-2ft-C-4000K-10W | ATS-LEDB-2ft-F-4000K-10W | ATS-LEDB-2ft-C-5000K-10W | ATS-LEDB-2ft-F-5000K-10W |
|--------------------------------|---------------------------|--------------------------|--------------------------|--------------------------|
| LED Bulb Specifications | | | | |
| Input Voltage | 100-277 VAC | | | |
| Power Factor | > 0.95 | | | |
| Wattage | 10 W | | | |
| Output Lumens | 1251 lm | 1118 lm | 1334 lm | 1200 lm |
| Efficacy | 111 lm/W | 112 lm/W | 115 lm/W | 103 lm/W |
| Color Rendering Index (CRI) | ≥ 82 | | | |
| Beam Angle | 120° | | | |
| Color Temperature | 4000K | | 5000K | |
| Length | 2' | | | |
| Lens | Clear | Frosted | Clear | Frosted |
| Base | G-13 medium bi-pin | | | |
| Lifespan | > 60,000 hours | | | |
| Installation Environment | Indoor | | | |
| Operating Temperature | -4 to 131°F (-20 to 55°C) | | | |

| | ATS-LEDB-4ft-C-4000K-15W | ATS-LEDB-4ft-F-4000K-15W | ATS-LEDB-4ft-C-5000K-15W | ATS-LEDB-4ft-F-5000K-15W |
|--------------------------------|---------------------------|--------------------------|--------------------------|--------------------------|
| LED Bulb Specifications | | | | |
| Input Voltage | 100-277 VAC | | | |
| Power Factor | > 0.90 | | | |
| Wattage | 15 W | | | |
| Output Lumens | 2144 lm | 1892 lm | 2140 lm | 1928 lm |
| Efficacy | 119 lm/W | 105 lm/W | 119 lm/W | 106 lm/W |
| Color Rendering Index (CRI) | ≥ 82 | | | |
| Beam Angle | 120° | | | |
| Color Temperature | 4000K | | 5000K | |
| Length | 4' | | | |
| Lens | Clear | Frosted | Clear | Frosted |
| Base | G-13 medium bi-pin | | | |
| Lifespan | > 60,000 hours | | | |
| Installation Environment | Indoor | | | |
| Operating Temperature | -4 to 131°F (-20 to 55°C) | | | |



The facts and figures herein are carefully compiled to the best of our knowledge and are intended for general informational purposes only. Responsibility for the use and application of AccelTex Solutions materials rests with the end user. All AccelTex Solutions products are sold pursuant to the AccelTex Solutions Terms and Conditions of Sale. © 2016 AccelTex Solutions. All Rights Reserved. AccelTex, AccelTex Solutions, the AccelTex Solutions Logo and other marks are trademarks or registered trademarks of AccelTex Solutions. Other products or service names may be the property of third parties.

1.888.406.8906
SALES@ACCELTEX.COM